

High Resolution Multibeam Systems for:

Hydrography

Offshore

Dredging

Defense

Research

R2Sonic LLC 5307 Industrial Oaks Blvd. Ste120 Austin, TX USA 78735

T: 512 891 0000

www.r2sonic.com

SONIC 2024

Wideband Multibeam Echo Sounder

Features:

- Focused Beams to 0.3° x 0.6°*
- Wideband 170 kHz 450 kHz
- 700 kHz Option
- Selectable swath sector 10° to 160°
- Swath sector rotation
- Sounding Depth to 400m+
- Embedded Processor/Controller
- Low Weight, Volume and Power



The Sonic 2024 is the world's first broadband - wideband high resolution shallow water multibeam echo sounder. With proven results and unmatched performance, the Sonic 2024 has become an industry standard, setting the bar in innovation and compelling customer value.

The Sonic 2024 provides user selectable operating frequencies between 170 kHz and 450 kHz to 1 Hz resolution, and optional 700 kHz, with unparalleled flexibility to trade off resolution and range and controlling interference from other active acoustic systems

In addition to selectable operating frequencies, the Sonic 2024 provides variable swath coverage selections from 10° to 160°, the ability to rotate the swath sector, as well as roll stabilization. Both the frequency and swath coverage may be selected 'on-the-fly', in real-time during survey operations.

The Sonar consists of the three major components: a compact and lightweight projector, a receiver and a small dry-side Sonar Interface Module (SIM). Third party auxiliary sensors are connected to the SIM.



The sonar operation is controlled from a graphical user interface on a PC or laptop typically equipped with navigation, data collection and storage applications software.

The operator sets the sonar parameters in the sonar control window, while depth, imagery and other sensor data are captured and displayed by the applications software.

Commands are transmitted through an Ethernet interface to the Sonar Interface Module. The Sonar Interface Module supplies power to the sonar heads, synchronizes multiple heads, time tags sensor data, and relays data to the applications workstation and commands to the sonar head. The receiver head decodes the sonar commands, triggers the transmit pulse, receives, amplifies, beamforms, bottom detects, packages and transmits the data through the Sonar Interface Module via Ethernet to the control PC.

The compact size, low weight, low power consumption 50W and elimination of separate topside processors make Sonic 2024 *very well suited* for small survey vessel, ROV or AUV operations.

200 kHz	450 kHz	700 kHz
1° x 2°	0.5° x 0.9°	0.3° x 0.6°

Beam widths at selected frequencies (nadir)

Sonic 2024 Multi Beam Echo Sounder

-30° C to 55° C

Systems Specification:

170 kHz-450 kHz & Frequency 700 kHz (optional)

Beamwidth, Across Track 0.3°* Beam Width, Along Track 0.6°* No. of Beams 256 Selectable Swath Sector 10° to 160° 400m+** Sounding Depth Pulse Length 15 μs-1115 μs Shaped CW Pulse Type Ping Rate Up to 60 Hz Depth Rating 100 m -10° C to 50° C Operating Temperature

Electrical Interface

Storage Temperature

90-260 VAC, 45-65 Hz Mains 50 W (Sonar Head) **Power Consumption** Uplink/Downlink: 10/100/1000Base-T

Ethernet

Data Interface 10/100/1000Base-T

Ethernet

280 x 170 x 60 mm

Sync In, Sync out TTL

GPS 1PPS, RS-232

Auxiliary Sensors RS-232 Deck Cable Length 15 m

Mechanical:

Receiver Dim (LWD) 480 x 109 x 190 mm

Receiver Mass 12.9 kg

273 x 108 x 86 mm Projector Dim (LWD)

Projector Mass 3.3 kg

Sonar Interface

Module Dim (LWH)

Sonar Interface Module Mass


2.4 kg

Sonar Options:


Snippets/TruePix Imagery Output Ultra-High Resolution UHR 700 kHz Switchable Forward Looking Sonar Output Raw Water Column Data Output Integrated Inertial Navigation System Integrated Sediment Profiler Mounting Hardware & Assemblies 4000/6000m Immersion Depth Ratings **Antifouling Coating Protection**



Sonar Interface Module



Sonic 2024 Receiver



Sonic 2024 Projector

High Resolution Multibeam Systems

Hydrography

Offshore

Dredging

Defense

Research

R2Sonic LLC 5307 Industrial Oaks Blvd. Ste 120 78735

T: 512 891 0000

www.r2sonic.com

^{*}Beam width to 0.3° x 0.6° with UHR 700 kHz option

^{**}Max sounding depths depend on environmental conditions